




Luxxor® Portable Video Camera *Connects to ANY Hawkeye® Rigid or Flexible Borescope!*

When connected to any Hawkeye Borescope, the new Luxxor Portable Video Camera delivers sharp, bright video and still images. Inspection images can be viewed "live," and captured!

LPC



3 Viewing Options:



Portable Video Monitor:
Portable video monitor with image capture PVM-DV



Computer Ready:
USB capture device with software VC-USB2



Sony® Professional Video Monitor:
15" LCD monitor SVM-15

LUXXOR® PORTABLE CAMERA SPECIFICATIONS

Image Sensor	1/4" Color CCD
Lens	Built in - 25mm Borescope coupler lens
Mount	Quick release, ball bearing mount couples borescope securely to the camera. Attaches to any standard 32 mm diameter borescope eyecup
Video Format	NTSC
Resolution	768 x 494 pixels (520 TV lines)
S/N Ratio	48DB +
Min. Illumination	0.2 Lux at F/1.2 (without borescope)
Shutter speed	1/50 - 1/100,000
Working Temperature	-10 to 45 deg C
Power Supply	5 - 12 V DC, 80 mA
Output	Standard cable is RCA composite video, or 12 Pin Hi-ROSE with portable video monitor
Dimensions	Length = 160mm Diameter, handle = 32mm , Diameter, coupler lens = 44.5mm

From the makers of:



PRECISION BORESCOPIES

Made in USA